

UL 10C POSITIVE FIRE RATINGS CERTIFIED BY WARNOCK HERSEY
 IDP Inc. ENTRY-FIT™ PREFINISHED STEEL DOOR FRAMES
 SINGLES AND PAIRED OPENINGS FOR 1-3/4" THICK DOORS

FIRE RATED PRODUCTS



ENTRY FIT™ FIXED THROAT FRAMES
F-SERIES NON KERFED and KF-SERIES KERFED FRAMES

Rating	Max Door Opening Width	Max Door Opening Height	Min Wall Size F-Series	Min Wall Size KF-Series	Frame Gauge	Test Standard	Edge Seals for Cat A Doors	Edge Seals for Cat B Doors
90 Min.	Single 3'6"	7'0"	4-1/2"	5"	18	Positive Pressure	No Additional Edge Seals Required	Additional Category H Edge Seals Required
90 Min.	Single 3'0"	8'0"	4-1/2"	5"	18	Positive Pressure	No Additional Edge Seals Required	Additional Category H Edge Seals Required
90 Min.	Pair 6'0"	8'0"	4-1/2"	5"	18	Positive Pressure	No Additional Edge Seals Required	Additional Category H Edge Seals Required

ENTRY FIT™ ADJUSTABLE WALL DOUBLE RABBET FRAMES- DOOR PREHANGABLE
K2A KERFED and NK2A-SERIES NON-KERFED

Rating	Max Door Opening Width	Max Door Opening Height	Min Wall Size	Base Frame Gauge	Closure Frame Gauge	Test Standard	Edge Seals for Cat A Doors	Edge Seals for Cat B Doors
90 Min.	Single 4'0"	7'0"	4-1/2"	18	22	Positive Pressure	No Additional Edge Seals Required	Additional Category H Edge Seals Required
90 Min.	Single 3'0"	8'0"	4-1/2"	18	22	Positive Pressure	No Additional Edge Seals Required	Additional Category I
90 Min.	Pair 6'0"	8'0"	4-1/2"	18	22	Positive Pressure	No Additional Edge Seals Required	Additional Category H Edge Seals Required

ENTRY FIT™ SIDELITE and TRANSOM ASSEMBLY FRAMES

Rating	Max Door Opening Width	Max Door Opening Height	Min Wall Size	Frame Gauge	Test Standard	Test Standard	Glass Type	Glazing Material	Max Glass Width	Max Glass Height	Max Assembly Width	Max Assembly Height
45 Min.	3'0"	8'0"	4-1/2"	18	PP	Positive Pressure	Wire	Listed	24"	94-1/2"	6'4"	9'2"
45 Min.	3'0"	8'0"	4-1/2"	18	PP	Positive Pressure	Wire	Listed	62"	12"	6'4"	9'2"
45 Min.	3'0"	8'0"	4-1/2"	18	PP	Positive Pressure	Wire	Listed	36"	12"	6'4"	9'2"
45 Min.	3'0"	8'0"	4-1/2"	18	PP	Positive Pressure	Ceramic	Listed	24"	94-1/2"	6'4"	9'2"
45 Min.	3'0"	8'0"	4-1/2"	18	PP	Positive Pressure	Ceramic	Listed	62"	12"	6'4"	9'2"
45 Min.	3'0"	8'0"	4-1/2"	18	PP	Positive Pressure	Ceramic	Listed	36"	12"	6'4"	9'2"

ENTRY FIT™ FIRE WINDOW/BORROWED LITE

Rating	Min Wall Size	Min Wall Size	Frame Gauge	Test Standard	Test Standard	Glass Type	Glazing Material	Glass Width	Max Glass Height	Assembly Width	Assembly Height
45 Min.	4-1/2"	4-1/2"	18	PP	Positive Pressure	Wire	Listed	36"	86"	6'2"	7'2"
45 Min.	4-1/2"	4-1/2"	18	PP	Positive Pressure	Wire	Listed	36"	60"	6'2"	7'2"
45 Min.	4-1/2"	4-1/2"	18	PP	Positive Pressure	Wire	Listed	36"	24"	6'2"	7'2"
45 Min.	4-1/2"	4-1/2"	18	PP	Positive Pressure	Ceramic	Listed	36"	86"	6'2"	7'2"
45 Min.	4-1/2"	4-1/2"	18	PP	Positive Pressure	Ceramic	Listed	36"	60"	6'2"	7'2"
45 Min.	4-1/2"	4-1/2"	18	PP	Positive Pressure	Ceramic	Listed	36"	24"	6'2"	7'2"